

---

**COMPOSITION / CONSTRUCTION of MATERIALS:**

**Doors** are 1" thick X **63.5" HIGH** constructed with two **22-gauge** sheets of stretcher leveled type 304 stainless steel #4 finish that are formed and then laminated under pressure to a sound deadening double-faced honeycomb core. Face plates are welded together at intervals of 18" on center around entire perimeter to insure a rigid one-piece unit. All edges are then interlocked with a continuous stainless steel roll-formed edge molding. All mitered corners are welded and ground smooth. Corner clips will not be acceptable.

**Panels** are 1" thick X **63.5" HIGH** constructed with two **22-gauge** sheets of stretcher leveled type 304 stainless steel #4 finish that are formed and then laminated under pressure to a sound deadening double-faced honeycomb core. Face plates are welded together at intervals of 18" on center around entire perimeter to insure a rigid one-piece unit. All edges are then interlocked with a continuous stainless steel roll-formed edge molding. All mitered corners are welded and ground smooth. Corner clips will not be acceptable.

**Type F/C -Floor to Ceiling Pilasters** are 1-1/4" thick, constructed with two **18-gauge** sheets of stretcher leveled type 304 stainless steel #4 finish that are formed and then laminated under pressure to a sound deadening double-faced honeycomb core. Face plates are welded together at intervals of 18" on center around entire perimeter to insure a rigid one-piece unit. Edges are then interlocked with a continuous stainless steel roll-formed edge molding. An inverted heavy gauge channel shall be welded into top and bottom of the pilaster for additional reinforcing. Pilasters are attached to finished floor and ceiling with stainless steel angle brackets. A polished 3" high stainless steel shoe of one-piece construction shall be supplied to conceal the floor and ceiling anchoring. Tamper proof shoe assembly held in place by means of concealed floor anchor clips –exposed screws are not acceptable.

**FINISH:** All doors, panels and pilasters shall be type 304 stainless steel with a #4 finish and include a durable plastic film covering to safeguard them during shipment and installation. All components shall have vertical #4 grain finish.

**HARDWARE and FITTINGS:** All material components are fully prepared with suitable internal reinforcement to receive all necessary hardware and fittings. All door hinges will be thru-bolted with sex bolts having theft resistant heads. Appropriate screws supplied for all other hardware and fittings. All fastenings to have a corrosion resistant finish.

***Doors:***

- Upper and lower door brackets are heavy non-ferrous Zamac castings that become integral part of door as they are imbedded within pre-formed abscesses at time of assembly. Satin finish shall closely resemble door finish.
- Top hinge bracket (#102) is a heavy, non-ferrous Zamac casting with chrome plated finish. One-piece design has a 5/8" wrap-around flange that fits over the pilaster edge for maximum durability.
- Stainless steel pin (#101) goes through the door and the top hinge bracket for three-point bearing.
- Bottom hinge bracket (#103) is a heavy, non-ferrous Zamac casting with chrome plated finish. One-piece design has a 5/8" wrap-around flange that fits over pilaster edge for maximum durability. Door operates on opposing nylon cams that are fully recessed and concealed within the lower door bracket. The gravity activated cam assembly provides easy adjustment of door permitting it to rest at any desired open or fully closed position when not latched.
- Concealed latch assembly with stainless steel pin allows for emergency access. Cover plate and turn knob (#104) are heavy, non-ferrous Zamac castings with chrome plated finish. ADA lever handles are supplied on all handicap doors.
- Combination coat hook and bumper for inswing doors (#106) or double-prong coat hook for outswing door (#107) shall be cast Zamac with chrome plated finish. Door pull (#109) shall be supplied on all outswing doors. ADA doors receive door pull on both interior and exterior faces. Door bumpers (#108) provided where required.
- **"No-sight"** aluminum hardware shall consist of a continuous privacy strip mounted between top & bottom hinges plus a continuous aluminum strike with keeper on latch side of all doors.

***Wall and Pilaster Brackets:***

- **Shall be continuous aluminum finish.** The wall anchored pilasters and dividing partition panels shall be attached with 62.5" high continuous aluminum channels. Dividing partition panels shall be attached to the "rear" pilaster face with a 62.5" continuous aluminum "U" channel. Wall supported only urinal screens shall be attached with a continuous double-ear aluminum wall bracket..

**INSTALLATION:** Shall be in accordance with AAMCO's approved shop drawing and installation instructions with partitions being rigid, plumb, straight and level. Unless stated otherwise, doors and panels are 63.5" high and mounted 6" above finished floor. Actual pilaster length is determined by ceiling height.

**WARRANTY:** AAMCO provides for all stainless steel materials, when properly maintained, a ten-year warranty against all defects in workmanship and construction under normal wear and use of this product.